



PROKLIMA



On behalf of



Federal Ministry for the
Environment, Nature Conservation
and Nuclear Safety

of the Federal Republic of Germany



INDUSTRY ROUNDTABLE

zero and low GWP HCFC alternatives

8-9 May, 2011, Male, Maldives

OPPORTUNITIES OF CLIMATE AND ENERGY EFFICIENCY CO-BENEFITS OF HCFC PHASE-OUT IN INDUSTRIAL REFRIGERATION

**SUSTAINABLE
INDUSTRIAL REFRIGERATION
AIR CONDITIONING SYSTEM
& HEAT PUMPS**

**LINE-UP NATURAL 5
FIELD CASES**

Mayekawa Mfg.Co,Ltd
Kunuaki Kawamura

Commitment on Natural Refrigerants



-  Semi-Hermetic Screw Compressor Unit
-  Commercial / Industrial Eco-Cute System
-  Adsorption Chiller
-  Commercial / Industrial
Air-Conditioning / Water-Supply Heat Pump
-  Dehumidifying Air Refrigerant System [Air Ref]

"Natural Five" Refrigerants and Product Solutions

Refrigerant (Natural Five)	NH ₃ R-717	CO ₂ R-744	HC Hydrocarbon	H ₂ O R-718	Air R-728
90°C		Utility hot water			
60°C	Utility hot water Heating		Utility hot water Heating HVAC	Heat recovery	
10°C	Chilled water Ice making	Chilled water Ice making		Chiller	
-15°C	Cold storage, Freezer, Fish boat				
-25°C	Specific Refrigeration needs				
-40°C	Freezer, Freeze-dry, Super Low temp storage				
-50°C					
-60°C			Cryogenics		Cryogenics
-100°C					
Notes	•Conventional system •National Projects	•Eco-Cute	•Nat'l Proj. •Butane + Propane	•Nat'l Proj. •Adsorption •Heat recovery	•Nat'l Proj. •Air-cycle

FIELD CASES

NH3

- High Efficiency: Compressors and IPM Motors
- Low Charge:
 - * Secondary Refrigerant System(CO2)
 - * Direct Expansion System
- Less Leakage: Hermetic Motors

Ammonia

NH3 + CO2 secondary brine

MYCOM

Semi-hermetic Refrigeration Package

2007 Ministry of the Environment
[Enterprise of Technical Development Against Global Warming]



MAYEKAWA
MAYEKAWA Europe nv/sa

DOC.2011-241 R3

Installation in Japan




Distribution center



30% Reduction of CO2 Emission


Hybrid Cooling System Using NewTon3000



Target : Industrial Refrigerated Warehouses (for Class F)

- **Improved Safety** : By developing [Semi-hermetic compressor], Mayekawa improved the problem of refrigerant leak.
- **Non-Freon** : A system in which ammonia circulates as the primary refrigerant and CO₂ as the secondary refrigerant.
- **Energy Saving** : As a unit exclusively for the refrigerated warehouse, CO₂ 2.0 at Class F. Compared to conventional Freon refrigerants, about 20% energy saving.

Efforts to Reduce CO2



Case Study

10,000t Refrigerated Warehouse
Inside Temperature: -25°C

Power Consumption

< Conventional System >

317kW

< Hybrid Cooling System >

222kW


NH₃

- **NH₃ Compression Refrigeration**


**Ammonia**

NH3 PISTON REFRIGERATION (15->1300 m3/hr)

MAYEKAWA Reciprocating compressors
Single-stage




MAYEKAWA Reciprocating compressors
Compound two-stage




NH3 SCREW REFRIGERATION (200->15.600 m3/hr)


MAYEKAWA Screw compressors
Single-stage



MYCOM SCREW COMPRESSORS LINE-UP
Single-stage (2)



MAYEKAWA Screw compressors
Compound two-stage





NH3 REFRIGERATION

MYCOM

- | | |
|--------------------------|--|
| • INSTALLATION | 2005 |
| • HOURS OPERATION | 30.000 hours |
| • APPLICATION | 80.000m ³ store |
| • OUTPUT NH ₃ | 1200kW -34°C NH ₃ |
| | CO ₂ (brine) 1200Kw -30°C CO ₂ |





- | | |
|-------------------|----------------------|
| • INSTALLATION | 2003 |
| • HOURS OPERATION | 28.000 hours |
| • APPLICATION | ice cream production |
| • Freezing output | 3450kW -42°C |

NH₃


- **NH₃ Compression Heat-Pump**

**Ammonia**





NH3 HEAT PUMPS

MYCOM



- | | |
|--------------------|-----------------|
| • INSTALLATION | 2008 |
| • HOURS OPERATION | 4.000 hours |
| • APPLICATION | meat processing |
| • Hot water output | 400kW 60°C |



- INSTALLATION 2009
- HOURS OPERATION 6.000 hours
- APPLICATION district heating
- Hot water output 2400kW 77°C



CO2

- Hot water and Hot dry air supply Heat-Pump
- Source : Air and Water

Carbon dioxide

Industrial Hot Water Production Package


Awarded for: The 7th Electric-Load Leveling Equipments / systems [Heat Pump Thermal Storage Development Awards]



Water-Source Type is also available.




62% Reduction of CO2 Emission



Targets: Hospitals, hotels, welfare institutions, sports facilities, bathing facilities, facilities for boarding, food factories, etc.

- The best water supply ability in Japan (Air heat source 80kW, water heat source 90kW).
- Very little CO₂ emission, compared with equipments run by burning the energy source. Emission could be cut by more than 60% than heavy-oil boilers.
- 循環 heating operation (Water entering Eco-Cute at 65°C, exiting at 90°C).
- Flexible design of water supply system and storage tanks to meet your needs.
- Entering medium to large-scale water supply market as the electric equipment replacing hot-water boilers. The complete electrification is possible.

Efforts to Reduce CO₂ Emission



Case Study


A Company Housing where Hot Water Supply is 20m³/day
The Number of People: 200

<Conventional System>	<Commercial Eco-Cute>
Fuel Oil Boiler	
Crude Oil Equivalent	Crude Oil Equivalent
59,040 ℓ /yr	22,153 ℓ /yr

CO2

- CO2 Compression Refrigeration

**Carbon dioxide**




A. LOW TEMP. SIDE : FREEZING CAPACITIES

CO2 LIQUID T°	1xGH160	2xC200WHD	2xC6HK
-51 °C	1300 KW	2900 KW	
-41 °C	1800 KW		800
-31 °C	2000 KW		1000

B. HIGH TEMP. SIDE

NH3

7 x SCREW COMPRESSORS



- INSTALLATION 2005
- HOURS OPERATION 38.000 hours
- APPLICATION meat industry



- Mixed Refrigerants Heat-Pump
(Butane and Propane)

Hydrocarbon

Hydrocarbon Refrigerant Packaged Unit

2005
~2007 NEDO [Energy-Saving Non-Freon Air-Conditioning and Refrigeration System]

[[Industrial Technology Development Subsidizing Company]]




14% Reduction of CO2 Emission

Cooling C O P	COP=3.7 (Air-Cooled)
Heating C O P	COP=3.7 (Air-Source)
Supplying Water C O P	COP=3.3 (Supplying temperature 65°C, air-source)

Targets: Commercial / Industrial Air-Conditioning, Water-Supply

Supply Temperature	Applications	Suitable Markets
70°C	65°C Hot Water-Supply / Heating System	Food factories, hotels
50°C	45°C Heating System	Office buildings, factories
0°C	+7°C Chilled Water Chiller System	Office buildings, factories
-5°C	+2°C Chilled Water Chiller / Supercooling Making System	Food factories
-15°C	Ice on Coil Ice Thermal Storage System	Food factories

Efforts to Reduce CO2 Emission



Case Study

40USRT Chilled Water Supply Machine
Chilled Water Temperature : 7°C

Power Consumption

< Conventional System >
R134a
Chilled Water Supply Machine
43kW

< Hydro Carbon >
36kW

A purple rounded rectangle with a white border containing the text "H2O".

H2O

- Ad-sorption Chiller Utilizing Solar Energy

A horizontal bar with a purple-to-white gradient, ending in a solid purple section on the right.

Water

Adsorption Chiller Packaged Unit


2005
~2007 NEDO [Research and Development of New System Utilizing Solar Energy]



Efforts to Reduce CO₂ Emission

(t-CO₂/year)

(Annual)



Case Study

100USRT Industrial Process Cooling
Cold Water Temperature : 9 °C

Power Consumption

<Conventional System>
R134a Cooling Water

100kW

<Adsorption Chiller>

36kW

AIR

- Air Cycle Refrigeration System
- For Low Temperature Applications
-50 ~ -120 °C


AIR

Air Cycle Refrigeration Packaged Unit

2003 Developed at [Technical Strategy for Rationalization of Energy Consumption Project]
~2005 NEDO




54% Reduction of CO2 Emission



Target: Ultra cold refrigerator for tunas and bonitos, rapid freezer, frost-破碎 etc.

- Using [Air] as the ultimate natural refrigerant, [Air Ref] is safe and eco-/people-friendly.
- Due to the turbo compressor with integrated expander, high COP can be achieved, saving energy by 50% comparing the conventional types.
- Due to its low operating pressure, exempt from legal regulations.
- Directly cooling the air, Air Ref does not require a fan coil unit or piping for refrigerant in the storage.
- Dihumidifying agent reduces frosting in the storage. Defrosting is not required.

Efforts to Reduce CO2 Emission



Case Study

2,000 ton Refrigerator
Interior Temperature : -60°C

Power Consumption

< Conventional System >
R22 2 Stage Compression Refrigerator

281kW

< Air Ref >

128kW

CONCLUSION

- MAIN GOAL :
‘zero and low GWP HCFC alternatives’
- GWP ‘NATURAL 5’ : 0 -> 3
- ODP ‘NATURAL 5’ : 0
- Field-examples : CO2 emission- & energy consumption reduction (approx.)

NH3 Newton3000	-30%
NH3 hot water	-60% (COP _h >2,5)
CO2 hot water	-62%
HC chilled water	-14%
ADSORPTION chilled water	-64%
AIR ultra cold air	-54%

**THANKS FOR YOUR
ATTENTION!**

For copy of paper and additional production information :

booth #203 in Hall B of the UNEP Ozone2Climate Technology Virtual Exhibition

MAYEKAWA Global Network

Over 70,000 Screw and Piston compressors running in more than 100 countries.

Worldwide:

- 33 countries / 119 offices
- 8 production plants



MAYEKAWA Europe Organization

MAYEKAWA Europe nv/sa

Leuvensesteenweg 605 1930 Zaventem Belgium

Tel.+32 2 757 90 75 Fax.+32 2 757 90 23 URL <http://www.mayekawa.eu> E-mail info@mayekawa.eu

SWITZERLAND	Rosenbergstrasse 31, CH – 6300, Zug Tel.+41 41 726 8626 Fax.+41 41 726 8620
SPAIN	Calle Montevideo 5,Nave 13 POL.Industrial Campoporroso 28806 Alcala de Henares, Madrid Tel.+34 91 830 0392 Fax.+34 91 830 0397
RUSSIA	House 3, Flat 54, Mytnaya St.,Moscow, 119049 Tel.+7 495 230 01 76 Fax.+7 495 230 21 12
GERMANY	Nürnberg Strasse 118, 97076 Würzburg Tel.+49 931 35 93 88-0 Fax.+49 931 35 93 88-20
FRANCE	9, Rue Michael Faraday , 78180 Montigny-Le-Bretonneux, Tel.+33 1 30 58 2600 Fax.+33 1 30 58 1937
United Kingdom	16 Oakhurst Gardens, Bexleyheath, Kent DA7 5JP Tel.+44 1322 433558 Fax.+44 1322 433164
BULGARIA	94, Hristo Botev Str.1202 Sofia Tel/ Fax +359 2 8319002
DUBAI	P.O.Box.61349, LOB. 11. No.126, Jebel Ali Free Zone, Dubai, U.A.E Tel. +971 4 887 2232 Fax.+971 4 887 2238
INDIA	1 st Floor, Balaji House, Nr.Mahalaxmi Heights, Mumbai-Pune Road, Pimpri, Pune-411 018 Maharashtra, India Tel. +91 20 2746 4537 Fax.+91 20 2746 4539
AUSTRALIA	Unit 2,44 McCauley Street Matraville NSW 2036 Australia DOC.2011-241 R3 Tel. +61 2 9695 7000 Fax.+61 2 9695 7001
NEW ZEALAND	30 Tui Street Othahuhu PO. Box 12106 Auckland New Zealand Tel. +64 9 276 2305 Fax. +64 9 276 2306

Japan Head Office

3-14-15 Botan Koto-ku, Tokyo 135-8482, JAPAN

TEL:(81)-3-3642-8181 FAX:(81)-3-3643-7094

E-mail:e-public@mayekawa.co.jp

Global web site <http://www.mayekawa.com/>