



MAYEKAWA SCREW COMPRESSOR

i-Series



FEATURES



1. Easy alignment

The flanged motor/compressor design provides a simple alignment solution

2. Built-in suction strainer and check valve

The built-in suction strainer and check valve allow for easy maintenance

3. Oil lubrication

The oil lubrication is achieved by differential pressure

4. Bearings

Roller bearings are incorporated in the compressor design

5. Capacity regulation

The capacity is regulated by solenoid valves in 3-steps (100%, 75%, 50%) on the i125 models Further regulation is possible by frequency inverted operation with a speed range of 1500 - 4500 rpm on the i125S and I160S models The i125M, i125L, i160M and i 160L models can operate in the speed range 1500 - 3600 rpm


6. Simple structure makes packaging easy

This compressor makes smart packaging possible using its simple piping design

7. High efficiency, low vibration and low noise

The use of Mayekawa's traditional screw rotor profile ensures a high efficiency, low vibration and a low noise level

DIMENSIONS



Model	Dimensions (mm)				
	L	W	H1	H2	H2 without eyebolt
i125S	906,5	550	280	519	448
i125L	976,5	550	280	519	448
i160S	969,5	684	300	445	N/A
i160M	1014,5	684	300	445	N/A
i160L	1059,5	684	300	445	N/A

CAPACITIES

Model	i125S		i1125L	
	Evaporating Temperature (°C)	Cooling Capacity (kW)	Absorbed Power (kW)	Cooling Capacity (kW)
0	184,2	36,7	274,8	53,4
-5	151,5	36,0	226,1	52,4
-10	135,1 *	37,0	201,6 *	53,9
-15	110,7 *	35,4	164,9 *	53,4
-20	90,0 *	34,0	133,0 *	52,9
-25	72,2 *	31,7	107,7 *	46,3

Remarks:

Refrigerant: NH₃, Speed: 2950 rpm, Tc = +35°C, Sh = 0K, Sc = 0K

* With DX-economizer

Model	i160S		i160M		i160L	
	Evaporating Temperature (°C)	Cooling Capacity (kW)	Absorbed Power (kW)	Cooling Capacity (kW)	Absorbed Power (kW)	Cooling Capacity (kW)
0	398	77	498	92	597	110
-5	327	75	410	91	491	108
-10	292 *	77	366 *	93	438 *	11
-15	240 *	74	300 *	89	359 *	106
-20	195 *	71	244 *	86	292 *	102
-25	157 *	67	196 *	81	235 *	96

Remarks:

Refrigerant: NH₃, Speed: 2950 rpm, Tc = +35°C, Sh = 0K, Sc = 0K

* With DX-economizer

SPECIFICATIONS

Items		model				
		i125S	i125L	i160S	i160M	i160L
Compressor weight *	kg	530	570	640	680	720
Flange type	IEC	FF400, FF500		FF600		
Speed (rpm)	min ¹	1500 - 4500	1500 - 3600	1500 - 4500	1500 - 3600	
Rotation direction	-	Clockwise looking onto the compressor drive shaft				
Displacement 50Hz/60Hz	m ³ /hr	197/237	296/356	415/499	519/624	622/749
Refrigerant		R717				
Design pressure	barG	26				
Capacity regulation	-	3-steps (100%, 75%, 50%)		3-steps (100%, 75%, 50%)		
Connections	-					
Suction flange		MYCOM 100A (4")		ANSI 300 # 5"		
Discharge flange	-	MYCOM 65A (2 1/2")		ANSI 300 # 3"		
Oil inlet port	-	Rc 1/2		Rc 1		
Economizer	-	Rc 3/8		RC 3/4		
Liquid injection	-	Rc 1/4		Rc 1/2		

* The weight includes the motor spacer flange (excl. the main drive motor)

Remarks:

For the limits of working temperature, pressure and speed, please refer to the "Instruction Manual"

WORLDWIDE

- 47 countries / 99 offices
- 11 production plants



MAYEKAWA EMEA Organization

ABU DHABI

Ali & Sons Business Center Office No. 201
Ali Khalfan Rashed Al Mutawa Al Dhahiri Bldg.
Plot no 29, Al Ain Road, Umm Al Nar
Tel. +971 2 5102151
Fax +971 2 5102571

DENMARK

Lindholm Havnevej 29, 5800 Nyborg
Tel. +45 31929000
Email: contact@mayekawa.dk

DUBAI

P.O. Box 61349, W-HOUSE
No. RA-08-UC05
Jebel Ali Free Zone Dubai, UAE
Tel. +971 4 8886363
Fax +971 4 8886373

EGYPT

New Cairo, 5th Settlement
North 90th St.
The 47th Building
Tel. +20 22 5062925
Fax +20 22 5032901

FRANCE (representative agent) Siège social

8, rue des Fontenelles
44140 Le Bignon
Tel. +33 1 30 582600
Fax +33 1 30 581937
<http://www.mayekawa.eu/fr>
E-mail: mayekawa.france@mayekawa.eu

South East Branch Office Refrigerant Division

Rue François Coli - Bâtiment H
33290 Blanquefort
Tel. +33 1 30 582600

West Branch Office Food Processing Division

20, Rue Ampère
22590 Pordic
Tel. +33 1 30589795
Fax +33 1 30581937

GERMANY Mayekawa Deutschland GmbH

Zum Buckesch 7a
48336 Sassenberg-Füchtorf
Tel. +49 (0) 5426 2989920

Vertrieb BRD/Österreich

Tel. +49 151 42628055
<http://www.mayekawa.de>
Email: info@mayekawa.de

HUNGARY

Mayekawa Hungary Engineering Kft

Köbányai út 10/A
2049 Diósd,
Tel. +36 23 545712
Fax +36 23 545715
<http://www.mayekawa.eu>
E-mail: hungary@mayekawa.eu

ITALY

Milan Office
Via Riccardo Lombardi 19/12
20153 Milano
Tel. +39 2 48929218
Fax +39 2 4531728

Bologna Office

Via Pradazzo 7 40012
Calerara di Reno
Tel. +39 51 726364
Fax +39 51 726804

MOROCCO

6, Allée des Cyprès
20250 Casablanca
Tel. +212 600 041241

POLAND

ul. Druskiennicka 8/10
60-476 Poznan
Tel. +48 61 8420738
Fax +48 61 8485837

SOUTH AFRICA

West End
Unit 3 Prime Park
Printers Way
Montague Gardens 7441
Tel. +27 21 5511434
Fax +27 86 5463618

SPAIN

Calle Montevideo 5, Nave 13 Pol.
Industrial Camporroso 28806
Alcala de Henares, Madrid Tel.
+34 91 8300392
Fax +34 91 8300397
<http://www.mayekawa.es>
E-mail: mayekawa@mayekawa.es

SWITZERLAND

Rosenbergstrasse 31
6300 Zug
Tel. +41 41 7268626
Fax +41 41 7268620
<http://www.mayekawa.ch>
E-mail: info@mayekawa.ch

TURKEY

Dünya Ticaret Merkezi
A/2 Blok Kat: 10 No. 325
Yeşilköy
Istanbul
Tel. +90 212 46536 31- 34
Fax +90 212 4653635

UKRAINE

Golosiiivska Street 17
Office 110
03039 Kiev
Tel. +38 (044) 251-46-62

UNITED KINGDOM


16 Oakhurst Gardens
DA7 5JP Bexleyheath, Kent
Tel. +44 1322 433558
Fax +44 1322 433164

Japan Head Office

3-14-15 Botan Koto-ku
Tokyo 135 8482, JAPAN
Tel. 81 3 3642 8181
Fax 81 3 3643 7094
E-mail e-public@mayekawa.co.jp

MAYEKAWA Europe nv/sa

Leuvensesteenweg 605
1930 Zaventem - Belgium
Tel. +32 2 7579075
Fax +32 2 7579023
<http://www.mayekawa.eu>
E-mail info@mayekawa.eu



Global web site <http://www.mayekawa.com/>